

## Single Deck Faucet with Temperature Mixing Valve

- Heavy-duty brass construction and polished chrome body
- Heavy-duty double O-Ring swivel spout

### Temperature Mixing Valve

**Description:** Temperature Mixing Valve allows faucet water temperature to be pre-set and can be installed on any deck mount single inlet faucet or pre-rinse unit and includes:

- Built-in adjustable flow controls
- Built-in ball checks
- ½" FEMALE NPT Outlet
- Universal ¼" NPT or ½" NPS MALE Inlet

Model No.	Spout Size (inches)	Wt. lbs.
101201B	3½" Gooseneck	4
101202B	5" Gooseneck	4
101203B	8½" Gooseneck	4
101206B	6	4
101208B	8	4
101210B	10	6
101212B	12	6
101214B	14	6
101216B	16	6
909020	Temperature Mixing Valve	2



## Automatic Electronic Deck Mount Mixing Faucet

- Heavy-duty brass construction and polished chrome body
- Sealed waterproof construction
- Reliable solid state electronic circuitry

### Valve features the following:

- Built-in adjustable flow controls
- An infrared sensor detects the presence of an object in front of the unit and turns water On and Off
- Universal ¼" NPT or ½" NPS MALE inlets

Model No.	Spout Size (inches)	Wt. lbs.
100201	3½" Gooseneck	10
100202	5" Gooseneck	10
100206	6	10



Specifications	
Power	Four DC AA Alkaline Batteries or AC/DC Alternately
Working Pressure	0.2 - 15kg/cm2
Ambient Temp. Range	2 - 90° Celsius
Sensing Distance	2 - 17 cm (default 17cm)
Sensing Range Set-Up	Digital
Response Time	0.3 - 0.6 seconds (default 0.3 seconds)
Off Delay Time	1 - 2 seconds ((default 1 second)
Fresh Battery Life Cycle	500,000 On/Off
Low Battery Indicator	Red LED Flash
Battery Weakness	Red LED on, CPU off