

Universal Nozzles

SINGLE SPOUTS

- Double O-Ring, swivel spout
- Brass Base, polished chrome finish
- ½" NPS MALE inlet
- Compression nut and washer attached

Model No.	Spout Size inches	Description	Weight lbs.
703101	3.5	Gooseneck spout	2
703102	5	Gooseneck spout	2
703103	8.5	Gooseneck spout	2
703106	6	Straight spout	2
703108	8	Straight spout	2
703110	10	Straight spout	2
703112	12	Straight spout	2
703114	14	Straight spout	2
703116	16	Straight spout	2



703103



703114

DOUBLE JOINTED SPOUTS

- Heavy-Duty Double O-Ring, swivel spout
- Six inch joint

Model No.	Spout Size inches	Description	Weight lbs.
2001CP01	3.5	Gooseneck spout	3
2001CP02	5	Gooseneck spout	3
2001CP03	8.5	Gooseneck spout	3
2001CP06	6	Straight spout length 6"	3
2001CP08	8	Straight spout length 8"	3
2001CP10	10	Straight spout length 10"	3
2001CP12	12	Straight spout length 12"	3
2001CP14	14	Straight spout length 14"	3
2001CP16	16	Straight spout length 16"	3
2001CP18	18	Spout length 18" (6" joint+12" spout)	3



2001CP18



550



551



560



561

Shanks

Model No.	Size & Finish	Outlet size (inches)	Inlet size inches	Wt. lbs.
550	Heavy-duty polished chrome finish, brass round shank	1 1/32 - 14 UNS FEMALE outlet	1/2 - NPS MALE	2
551	Heavy-duty polished chrome finish, brass - 2 7/8" long hex shank with adjustable forged brass hex flange nut attached	1/8 NPT FEMALE outlet on hex shank and 1 1/32 - 14 UNS FEMALE outlet	1/2 - NPS MALE	2
560	Heavy-duty polished chrome finish, brass round shank with adjustable forged brass hex flange nut attached	1 1/32 - 14 UNS FEMALE outlet	1/2 - NPS MALE	2
561	Heavy-duty polished chrome finish, brass - 2 7/8" long hex shank with adjustable forged brass hex flange nut attached	1/8 NPT FEMALE outlet on hex shank and 1 1/32 - 14 UNS FEMALE outlet	1/2 - NPS MALE	2