

# Door & Drawer Upright



Model No.	Temp	Doors/Drawers	Capacity cubic feet	No. of Shelves	HP	Volts	Amps	Dimensions L x D x H*	Weight lbs.
TSR1D2	REF	1 (half) 2 (drawers)	23	1	1/3	115	4.94	29.25" x 31.75" x 79.25"	328
TSR2D2	REF	1 (full) 1 (half) 2 (drawers)	48	4	1/3	115	5.30	49.75" x 31.75" x 79.25"	423
TSR2D4	REF	2 (half) 4 (drawers)	48	2	1/3	115	5.30	49.75" x 31.75" x 79.25"	465
TSRF2D2	DUAL	1 (full) 1 (half) 2 (drawers)	22R + 22F	4	1/3 REF 1/2 FZR	115	12.49	49.75" x 31.75" x 79.25"	503
TSWQ2D2	DUAL	1 (full) 1 (half) 2 (drawers)	39R + 13F	4	1/3 REF 1/3 FZR	115	12.24	59" x 31.75" x 79.25"	573

\*Height dimension includes casters ■ Sizes nominal, specifications subject to change without notice.




TSR1D2




TSR2D2



TSR2D4



TSRF2D2



TSWQ2D2

## Standard Features

### Cabinet Construction

Heavy duty stainless steel, and galvanized steel finished top, bottom and back wall of exterior. High quality 304 stainless steel interior, ABS evaporator drain cover. Insulated with 2.5" thick high density foamed-in-place polyurethane foam. Four 4" diameter casters (front casters with brakes). Door and drawer heater installed around inside cabinet frame to prevent moisture build up.

### Refrigeration System

- Self-contained condensing unit located at top of cabinet for high performance
- Oversized condenser and evaporator coil cools to set temperature in a minimum time period and maintains it
- Environmentally friendly CFC free R-134A and R-404A refrigerant
- Adjustable defrost cycle between every 3 to 12 hours with 400 watt heater, time initiated, and both temperature and time terminated for fail-safe backup
- Automatic evaporator fan motor delay on defrost cycle
- Copper tube and aluminum fin evaporator with anti-corrosive coating
- Energy efficient condensate drain pan located at bottom of cabinet constructed of anodized aluminum
- Two pressure relief ports located at exterior back wall and top of cabinet for rapid re-entry
- Interior airflow backguard to ensure proper air circulation
- Pre-wired and ready to plug to, 115V/60Hz/1Ph, NEMA 5-15P

### Doors & Drawers

- 430 stainless steel exterior with 304 stainless steel interior
- Insulated with 2.5" thick foamed-in-place polyurethane foam
- Rounded corners for a sleek and modern appearance
- Heavy duty adjustable torsion spring self-closing door system
- One piece snap-in magnetic door gasket for easy replacement
- Heavy duty recessed door handles that stay out of the way
- Heavy duty 304 stainless steel drawer frames and low friction bearing slides
- Door locks

### Lighting

- Safety shielded incandescent interior lighting

### Shelving

- Three epoxy coated wire shelves per full door, one shelf per half door
- 304 stainless steel pilasters and shelf clips

### Temperature Control

- Factory preset temperature, 35° F for refrigerator and -4° F for freezers
- Setting temperature range from 33° F to 41° F for refrigerator and -10° F to 32° F for freezers
- Easy to read digital temperature display
- Easy to control temperature by simply pushing buttons on control box
- Microchip digital monitoring system provided with various functions for monitoring and maintaining ideal temperature