

Glass Door Refrigerators

SLIDING DOORS



TMGR33

TMGR48

TMGR69

SWINGING DOORS



TMSGR24

TMSGR33

TMSGR48

TMSGR69



Options:

4" or 2.5" diameter casters
(5" and 3" overall height)

Standard Features and Benefits:

- Heavy duty white coated steel cabinet, stainless steel floor, black PVC door frames and black coated steel front grill exterior
- Insulated with 2.5" thick high density foamed in place polyurethane foam
- Adjustable screw legs for leveling; one extra on GR69 to support middle weight
- Oversized bottom mount slide out condensing unit for easy maintenance and repair
- Four Adjustable epoxy coated wire shelves and 304 stainless steel shelf clips
- Double pane glass system with a layer of transparent thermal insulating film between two layers
- Removable self-closing sliding doors on stainless steel track for easy cleaning
- Self-closing swing doors on heavy duty adjustable torsion spring with snap-in magnetic door gasket and heavy duty handle
- Safety shielded vertical fluorescent interior lighting with on/off switch
- Evaporator copper tube with anti-corrosive coating
- CFC free R-134a refrigerant
- Condensate drain pan included
- Factory preset temperature 35° F with dial thermostat knob

Model No.	No. of Doors	Type of Doors	Capacity (Cu. Ft.)	No. of Shelves	HP	Volts	Amps	Dimensions L x D x H	Weight lbs.
TMSGR24	1	Swing	24	4	1/3	115	4.07	28.5" x 33.5" x 79.25"	240
TMGR33	2	Sliding	33	8	1/3	115	4.16	39.5" x 30.75" x 79.25"	403
TMSGR33	2	Swing	33	8	1/3	115	4.16	39.5" x 33.5" x 79.25"	403
TMGR48	2	Sliding	48	8	1/2	115	9.00	53.25" x 30.75" x 79.25"	531
TMSGR48	2	Swing	48	8	1/2	115	9.00	53.25" x 33.5" x 79.25"	494
TMGR69	3	Sliding	69	12	1/2	115	11.00	73" x 30.75" x 79.25"	650
TMSGR69	3	Swing	69	12	1/2	115	11.00	73" x 33.5" x 79.25"	670

* Depth of swing door includes 1.5" for door handle ▪ Sizes nominal, specifications subject to change without notice.

Ice Cream Freezers

Standard Features and Benefits:

- Heavy duty white coated steel for cabinet interior and exterior, 304 series stainless steel floor interior, and aluminum door frames
- High density foamed-in-place polyurethane foam insulation
- Triple pane glass door system with layer of transparent thermal insulating and heating film
- Positive seal self-closing doors with single piece magnetic door gasket design
- Heavy duty epoxy coated shelves standard
- Hot gas defrost cycle system
- Evaporator constructed of copper tubing and aluminum fins, assembly treated with anti-corrosive coating
- Door heater installed around inside cabinet frame to prevent moisture build-up
- Illuminated signboard and interior
- Carel microchip digital control system with LED temperature display



TMSGF32

Model No.	No. of Doors	Type of Doors	Capacity (Cu. Ft.)	No. of Shelves	HP	Volts	Amps	Dimensions L x D x H	Weight lbs.
TMSGF17	1	Swing	17	4	3/4	115	10.5	26.38" x 30.83" x 78.35"	260
TMSGF20	1	Swing	20	4	3/4	115	10.5	29.13" x 31.61" x 78.35"	280
TMSGF32	2	Swing	32	8	1	230	7.0	40.94" x 31.61" x 78.35"	440

Sizes nominal, specifications subject to change without notice.