

Solid Door Under Counter Refrigerators, Freezers and Dual Temps




CTUR-2-48BM



CTUCFF-248



Back Mount Compressor



CTUR-1-27BM CTUR-2-36BM CTUR-2-48BM CTUR-2-60BM CTUR-2-72BM
CTUF-1-27BM CTUF-2-36BM CTUF-2-48BM CTUF-2-60BM CTUF-2-72BM

Standard - Side Mount Compressor



CTUCRR-136 CTUCRR-248 CTUCRF-260 CTUCRF-372
CTUCFF-136 CTUCFF-248

Model No.	Temp	Doors	No. Of Shelves	Capacity (Cu. Ft.)	HP	Volts	Amps	Dimensions L x D x H*	Door Width	Weight lbs.
Back Mount Compressor										
CTUR-1-27BM	REF	1	2	5.6	1/5	115	4.1	27.5" x 31.5" x 34.75"	26.5"	190
CTUF-1-27BM	FZR	1	2	5.6	1/3	115	5.2	27.5" x 31.5" x 34.75"	26.5"	180
CTUR-2-36BM	REF	2	4	7.5	1/5	115	4.4	35.5" x 31.5" x 34.75"	17"	220
CTUF-2-36BM	FZR	2	4	7.5	1/2	115	6.4	35.5" x 31.5" x 34.75"	17"	220
CTUR-2-48BM	REF	2	4	10.3	1/5	115	4.4	47.5" x 31.5" x 34.75"	22.75"	290
CTUF-2-48BM	FZR	2	4	10.3	1/2	115	6.4	47.5" x 31.5" x 34.75"	22.75"	290
CTUR-2-60BM	REF	2	4	15	1/4	115	4.7	59.5" x 31.5" x 34.75"	28.5"	300
CTUF-2-60BM	FZR	2	4	15	1/2	115	7.5	59.5" x 31.5" x 34.75"	28.5"	304
CTUR-3-72BM	REF	3	6	18.3	1/3	115	5.2	71.5" x 31.5" x 34.75"	22.75"	337
CTUF-3-72BM	FZR	3	6	18.3	1/2	115	7.67	71.5" x 31.5" x 34.75"	22.75"	342
Side Mount Compressor - Digital Temperature Read Out Included										
CTUCRR-136	REF	1	2	9	1/5	115	3.0	35.5" x 31.5" x 34.5"	22.75"	230
CTUCFF-136	FZR	2	2	9	1/3	115	4.4	35.5" x 31.5" x 34.5"	22.75"	240
CTUCRR-248	REF	2	4	13	1/5	115	3.0	47.5" x 31.5" x 34.5"	17"	270
CTUCFF-248	FZR	2	4	13	1/2	115	7.5	47.5" x 31.5" x 34.5"	17"	280
CTUCRF-260	DUAL	2	4	9R + 9F	1/2	115	7.6	59.5" x 31.5" x 34.5"	22.75"	330
CTUCRF-372	DUAL	3	6	14R + 8F	1/2	115	8.12	71" x 31.5" x 34.5"	18.75"	380

*Height dimension includes casters ▪ Sizes nominal, specifications subject to change without notice.

Standard Features and Benefits:

- Heavy duty stainless steel interior and exterior cabinet construction, including top, with galvanized steel exterior bottom and back wall, 4" diameter casters – two with brakes
- Insulated with 2.5" thick high density foamed in place polyurethane foam
- Available back or side mount compressor with slide out condensing unit for easy maintenance and repair (back mount units front breathing)
- CFC free R-134A or R-404A refrigerant, evaporator copper tube with anti-corrosive coating
- Condensate drain pan included
- Recessed handle, self closing doors with heavy duty adjustable torsion spring, magnetic gasket and door heater around cabinet frame
- Adjustable epoxy coated wire shelves – two per section - with stainless steel clips